(10) Patent No.:

US 6,626,305 B2 *Sep. 30, 2003

(45) Date of Patent:

3,628,844	Α	٠	12/1971	Preston 312/305
4,433,885	٨		2/1984	Baker
4,486,106	Α	*	12/1984	Benting 384/248
4,572,595	Α		2/1986	Craig
4,587,908	Α		5/1986	DeBruyn
4,616,940	Α		10/1986	DeBruyn
4,688,686	Α	•	8/1987	Mitts et al 211/183
4,819,900	Α	٠	4/1989	Funk 248/244
5,050,746	Α	•	9/1991	Frankel 211/34
5,287,869	Α	•	2/1994	Wu 135/25.1
5,312,003	Α		5/1994	Domenig
5,354,025	Α	•	10/1994	McCaffrey 248/188
5,494,346	Α		2/1996	Domenig
5,702,198	Α	•	12/1997	Kuo 403/377
5,931,315	Α		8/1999	Lorentz et al 211/40
5,941,399		*	8/1999	Wang 211/187
6,017,108	Α		1/2000	Domenig

* cited by examiner

Primary Examiner-Gregory J. Strimbu

(57)

ABSTRACT

A rotary shelf assembly mechanism has shelves mounted on a vertical post arrangement formed by a first lower post and a second upper post. The mechanism is connected to a cabinet by upper and lower mounting brackets interacting with the top and bottom of the cabinet to support the posts and shelves carried thereby. The mechanism is mounted in the corner of the cabinet. To fit the mechanism within the cabinet, a height adjustment device is formed by positioning the second upper post in the upper end of the first lower post for slidable movement therebetween. When securement of the two joined posts and mounted shelves is desired, the slidably movable second upper post is extended upwardly until it engages the upper mounting bracket mounted on the cabinet. An elongated recess in the second upper post aligns with an opening in the first lower post, and a threaded member extends into a casting positioned within the upper post. The threaded member is tightened to engage the casting and secure the two posts in a shelf-retaining and rotational mode. The height adjustment device enables quick and efficient installation of the mechanism within the cabinet interior. The mechanism also includes a one piece shelf construction having a post-securing section and a shelfretaining pin.

4 Claims, 10 Drawing Sheets

